
Art.-Nr: PMW423DL
Emergency light
Universal, DALI, 3 h, IP65, Polycarbonate, White, Flexiklick



Polycarbontate safety luminaire with convex shaped cover.

To help with mounting, levelling screws are integrated to compensate for uneven surfaces.

The luminaire can be mounted by fitting on the wall and ceiling as well as fitting in the ceiling in conjunction with the mounting frame available.

Central control and monitoring with standardized fieldbus DALI 2 The luminaire is fitted with the innovative **flexible plug-in system** for rapid use of the right lens. The corridor lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.


More information
www.rp-group.com/en/item/PMW423DL

TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	Waste disposal, CE, D-sign, HACCP (food law conformity)
Insulation class	2
Monitoring	DALI
Bridging time	3 h
Battery	LiFePO4 3,2 V/3,3 Ah
Input voltage AC	230 V - 240 V
Power max.	6,7 W
Power maintained	5,2 W
Power non-maintained	1,0 W
Ambient temperature maintained mode	-5 °C to 40 °C

Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	65 mm
Width	236 mm
Height	136 mm
Weight	0.71
Weight incl. packaging	0.84
Connection cross-section	2,5 mm²
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
GTIN	4262484980858

TECHNICAL DRAWING



ACCESSORY LIST

PME - Professional module housing for sophisticated electrical engineering

LSYS-B4 - Precision beam lens for accent lighting of safety devices

LSYS-F4 - Precise corridor lens for emergency exit and corridor lighting

LSYS-H4 - H-lens Special optics for emergency lighting in escape and rescue routes (installation height from 4 m)

LSYS-R4 - High-performance round lens for uniform emergency light distribution in open areas

LSYS-S4 - Precision spot lens for emergency lighting in large areas and high ceilings

LSYS-WF4 - Precise wall-corridor lens – Optimal light control for safety lights

As of: 16.11.2026 - Subject to technical changes and errors.