Art.-Nr: EERL433DL
Emergency light
Ceiling mounting, DALI, 3 h, IP20, Zinc die-cast, White, Flexiklick round & corridor



High-grade zinc-aluminium safety luminaire for fitting in the ceiling.

The compact design permits mounting in a 68mm opening in the ceiling. Alongside the usual recessed ceiling mounting, it can also be mounted in conventional and fire protection sockets. It is secured with ease using tension springs or a screw connection on the box.

Central control and monitoring with standardized fieldbus DALI 2 The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and corridor lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.

CE

More information
www.rp-group.com/en/item/EERL433DL


TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	2
Monitoring	DALI
Bridging time	3 h
Battery	LiFePO4 3,2 V/1,2 Ah
Power max.	4,2 W
Power maintained	3,6 W


Power non-maintained	0,9 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Height	4 mm
Diameter	88 mm
Installation height	100 mm
Installation dimensions Diameter	68 mm
Weight	0.25
Weight incl. packaging	0.38
Connection cross-section	2,5 mm²
Luminous flux mains	235 lm
Luminous flux emergency	235 lm
Customs tariff number	94056180
GTIN	4262484980933

TECHNICAL DRAWING


Maße EER / EEQ




Einzelbatterie-Elektronik-Box (UH-1)




Lochausschnitt EER / EEQ



Einsatz in U-Putzdose: 68mm
Einzelbatterie mit UH-1: 74mm



Schalterdose notwendig (nicht im Lieferumfang enthalten)



As of: 26.10.2026 - Subject to technical changes and errors.