

RP-Technik GmbH  
 Hermann-Staudinger-Straße 10-16  
 63110 Rodgau

Operator RP Projektteam  
 Telephone 06106 660280  
 Fax  
 e-Mail info@rp-group.com

## RP-TECHNIK WEF028SC-AZ Exit Sign recessed, SB + SC/8h / Data sheet emergency lighting



Luminaire: RP-TECHNIK WEF028SC-AZ Exit Sign recessed, SB + SC/8h

Lamps: 1 x WEF028SC-AZ

|  |        |
|--|--------|
| Colour rendering index:                | 70     |
| Luminous flux:                         | 270 lm |
| Correction Factor:                     | 1.000  |
| Emergency lighting factor:             | 1.00   |
| Emergency lighting luminous flux:      | 270 lm |
| Light output ratio:                    | 70.40  |
| Light output ratio (lower hemisphere): | 97.88  |
| Light output ratio (upper hemisphere): | 2.12   |

Glare valuation (Maximum luminous intensity [cd])

|                 | C0   | C90 | C0 - C360 |
|-----------------|------|-----|-----------|
| Gamma 60° - 90° | 88.2 | 1.9 | 131.6     |
| Gamma 0° - 180° | 88.2 | 2.5 | 131.6     |



Distance table for even escape routes

Mounting Height [m]

| 2.50 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
|------|------|------|------|------|------|
| 3.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3.50 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4.50 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 5.50 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 6.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 6.50 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 7.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

The spacing table is based on the following parameters:

- Maintenance factor: 0.80
- Emergency lighting factor: 1.00
- Minimum illuminance on centre line: 1.00 lx
- Minimum illuminance on half of escape route width: 0.50 lx
- Diversity on the centre line max. 40 : 1
- Width of escape route: 2.00 m



