



## Art.-Nr: 1LF15003SC-NW



LED Emergency luminaire for illuminating the escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

The robust wall and ceiling lamp made of fiberglass reinforced polyester for moisture-proof applications. The exterior smooth PMMA enclosure and installation friendly lever locks allow easy assembly.

Automatic monitoring of safety luminaire with SelfControl.



More information

[www.rp-group.com/en/item/1LF15003SC-NW](http://www.rp-group.com/en/item/1LF15003SC-NW)



### TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	NIMH 4,8 V/4,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	28,5 W
Power maintained	25,0 W
Power non-maintained	2,0 W
Ambient temperature maintained mode	-5 °C to 35 °C



Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	101 mm
Width	1573 mm
Height	108 mm
Weight	3.4
Weight incl. packaging	3.6
Connection cross-section	1.5 mm <sup>2</sup>
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	3300 lm
Luminous flux emergency	300 lm
Customs tariff number	94054940
EAN	4260682141279

## TECHNICAL DRAWING



As of: 16.05.2025 - Subject to technical changes and errors.