



Art.-Nr: 1LF15009-NW



LED Emergency luminaire for illuminating the escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

The robust wall and ceiling lamp made of fiberglass reinforced polyester for moisture-proof applications. The exterior smooth PMMA enclosure and installation friendly lever locks allow easy assembly.



More information

www.rp-group.com/en/item/1LF15009-NW




TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Bridging time	CPS
Battery	/
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V
Power max.	27,1 W
Power maintained	27,1 W
Power non-maintained	1,2 W
Ambient temperature maintained mode	-20 °C to 40 °C
Ambient temperature non-maintained mode	-20 °C to 40 °C
Depth	101 mm



Width	1573 mm
Height	108 mm
Weight	3.37
Weight incl. packaging	3.57
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	3250 lm
Luminous flux emergency	3250 lm
Customs tariff number	94054940
EAN	4260659561321

TECHNICAL DRAWING



As of: 16.05.2025 - Subject to technical changes and errors.