



**Art.-Nr: AGCC401WL**  
**Exit sign Self-contained**  
**Rope ceiling installation, Wireless Professional (WL), 1 h,**  
**50m, IP20, Zinc die-cast, White**

Modern zinc die-cast emergency exit sign luminaire with wire suspension for recessed mounting in the ceiling. Escape and emergency routes can be identified on either one or two sides.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Two requested pictograms (arrow to the right, left, up, down or white) are supplied as standard.



More information

[www.rp-group.com/en/item/AGCC401WL](http://www.rp-group.com/en/item/AGCC401WL)



## TECHNICAL DATA

| Luminaire type         | Exit sign                   |
|------------------------|-----------------------------|
| Mounting               | Rope ceiling installation   |
| Recognition distance   | 50m                         |
| Pictograph             | acc. to Specification       |
| Illuminant             | LED                         |
| Housing material       | Zinc die-cast               |
| Housing color          | White                       |
| Protection type (IP)   | IP20                        |
| Impact resistance (IK) | ≥ 3                         |
| Certification          | WEEE, CE, 5 years warranty  |
| Insulation class       | 2                           |
| Supply                 | Self-contained              |
| Monitoring             | Wireless Professional (WL)  |
| Bridging time          | 1 h                         |
| Battery                | LiFePO4 6,4 V/1,2 Ah        |
| Operating mode         | Non-maintained / maintained |
| Input voltageAC        | 230 V                       |



|   |                     |
|---|---------------------|
| Input frequency                         | 50 Hz               |
| Power max.                              | 7 W                 |
| Power maintained                        | 5,6 W               |
| Power non-maintained                    | 0,8 W               |
| Ambient temperature maintained mode     | -5 °C to 40 °C      |
| Ambient temperature non-maintained mode | -5 °C to 40 °C      |
| Depth                                   | 79 mm               |
| Width                                   | 512 mm              |
| Height                                  | 309 mm              |
| Installation length                     | 176 mm              |
| Installation width                      | 68 mm               |
| Installation height                     | 40 mm               |
| Weight                                  | 2.62                |
| Weight incl. packaging                  | 3.27                |
| Connection cross-section                | 2.5 mm <sup>2</sup> |
| Switching input                         | Yes                 |
| Emergency light blocking                | Yes                 |
| Battery connection                      | Connector           |
| Dimming function                        | Yes                 |
| Customs tariff number                   | 94056180            |
| EAN                                     | 4260682154286       |



## TECHNICAL DRAWING



As of: 16.04.2025 - Subject to technical changes and errors.