



## Art.-Nr: AIE009ML-AZ Exit sign Centralised power supply systems Ceiling mounting, Central power supply (ML), CPS, 15 m, IP20, Zinc die-cast, Anthracite

Modern zinc die-cast emergency exit sign luminaire for recessed mounting in the ceiling. With an installation diameter of 68 mm, this luminaire can be easily integrated into many environments. Escape and emergency routes can be identified on either one or two sides.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Control and monitoring via central power supply system. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.





More information www.rp-group.com/en/item/AIE009ML-AZ



## **TECHNICAL DATA**

Luminaire type	Exit sign
Mounting	Ceiling mounting
Recognition distance	15 m
Pictograph	Set
Illuminant	LED
Housing material	Zinc die-cast
Housing color	Anthracite
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching







Input voltage AC	230 V			
Input frequency	50 / 60 Hz			
Input voltage DC	216 V			
Power max.	2,25 W			
Power maintained	2,25 W			
Power non-maintained	0,7 W			
Ambient temperature maintained mode	-35 °C to 40 °C			
Ambient temperature non-maintained mode	-35 °C to 40 °C			
Depth	92 mm			
Width	167 mm			
Height	159 mm			
Installation dimensions Diameter	68 mm			
Weight	0.54			
Weight incl. packaging	0.79			
Connection cross-section	2.5 mm²			
Switching input	No			
Emergency light blocking	No			
Battery connection	No			
Dimming function	No			
Customs tariff number	94056180			
GTIN	4260581713355			






## TECHNICAL DRAWING











## RELATED PRODUCTS

ArtNo.	lmage	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
AIE009ML	<b>₹</b>	Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central
AIE009ML-E	<b>₹</b>	Central power supply (ML)	Central power supply	Edelstahl	€€€	Yes	low	Yes	1,920 per system	central
AIE509CC	<b>₹</b>	CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central
AIE509CC-AZ	<b>₹</b>	CoreCompact 24 (CC)	Central power supply	RAL 7016	€€	Yes	low	Yes		central
AIE509CC-E	<b>₹</b>	CoreCompact 24 (CC)	Central power supply	Edelstahl	€€	Yes	low	Yes		central

As of: 14.12.2025 - Subject to technical changes and errors.