



Art.-Nr: AIR009ML-AZ Exit sign Centralised power supply systems Recessed wall mounting, Central power supply (ML), CPS, 15 m, IP40, Zinc die-cast, Anthracite

Modern zinc die-cast emergency exit sign luminaire for recessed mounting in the wall and for identifying emergency and escape routes.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Control and monitoring via central power supply system. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.





More information

www.rp-group.com/en/item/AIR009ML-AZ



TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Recessed wall mounting
Recognition distance	15 m
Pictograph	Set
Illuminant	LED
Housing material	Zinc die-cast
Housing color	Anthracite
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching
Input voltageAC	230 V







Input frequency	50 / 60 Hz				
Input voltage DC	216 V				
Power max.	2,25 W				
Power maintained	2,25 W				
Power non-maintained	0,7 W				
Ambient temperature maintained mode	-35 °C to 40 °C				
Ambient temperature non-maintained mode	-35 °C to 40 °C				
Depth	58 mm				
Width	167 mm				
Height	118 mm				
Installation dimensions Diameter	68 mm				
Weight	0.54				
Weight incl. packaging	0.79				
Connection cross-section	2.5 mm²				
Switching input	No				
Emergency light blocking	No				
Battery connection	No				
Dimming function	No				
Customs tariff number	94056180				
EAN	4260581713447				







TECHNICAL DRAWING













RELATED PRODUCTS

ArtNo.	lmage	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
AIR009ML	₹ }	Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central
AIR009ML-E	₹	Central power supply (ML)	Central power supply	Edelstahl	€€€	Yes	low	Yes	1,920 per system	central
AIR509CC	₹ }	CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central
AIR509CC-AZ	₹	CoreCompact 24 (CC)	Central power supply	RAL 7016	€€	Yes	low	Yes		central
AIR509CC-E	₹	CoreCompact 24 (CC)	Central power supply	Edelstahl	€€	Yes	low	Yes		central

As of: 17.05.2025 - Subject to technical changes and errors.