Exit sign
Art.-No.: AMW009-AZ

The AMW is a zinc-diecast exit sign for wall mounting and for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaires of the A-Series are equipped with modern LED illuminants and offer flexibility with changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838

TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Wall mounted
Viewing distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Zinc die-cast
Colour	RAL 7016
Mechanical rating IP	40
Impact resistance IK	≥ 3
Protection class	2
Supply	Central power supply system
Monitoring	None
Operation time	CPS
Operation mode	Maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	100-254 V
Power consumption max.	2,4 W
Power consumption maintained	2,4 W
Power consumption non-maintained	0 W
Ambient temperature maintained mode	-25 °C / 40 °C
Ambient temperature non-maintained mode	-25 °C / 40 °C
Length	50 mm
Width	236 mm

Height	151 mm
Weight	1.22 kg
Weight incl. Packaging	1.58 kg
Connection cross-section	1.5 mm
Switching input L'	No
Emergency light blocking	No
Battery connector	None
Dimming function	No
Customs tariff number	94056180
Coutry of origin	Germany
EAN	4260581714819

TECHNICAL DRAWING



ACCESSORIES

BALLPLX-AM - Ball protection 330x250x77mm incl. fastening

AM-X-APA - Surface mounting adapter for lateral cable feed