



### Art.-Nr: AMWA003SC-E Exit sign Self-contained Wall construction flag, SelfControl (SC), 3 h, 22 m, IP40, Zinc die-cast, Stainless steel

Modern zinc die-cast emergency exit sign luminaire for surface mounting on the wall. Thanks to the wall bracket, the escape and emergency routes are identified at right angles to the wall. This can be done on either one or two sides.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



( (

More information www.rp-group.com/en/item/AMWA003SC-F



#### **TECHNICAL DATA**

Luminaire type	Exit sign
Mounting	Wall construction flag
Recognition distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Zinc die-cast
Housing color	Stainless steel
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained
Input voltageAC	230 V







Input frequency	50 / 60 Hz				
Power max.	4,7 W				
Power maintained	4,7 W				
Power non-maintained	1,95 W				
Ambient temperature maintained mode	-5 °C to 40 °C				
Ambient temperature non-maintained mode	-5 °C to 40 °C				
Depth	80 mm				
Width	334 mm				
Height	196 mm				
Weight	1.6				
Weight incl. packaging	1.96				
Connection cross-section	2.5 mm <sup>2</sup>				
Switching input	Yes				
Emergency light blocking	Yes				
Battery connection	Connector				
Dimming function	Yes				
Customs tariff number	94056180				
EAN	4260581714642				





# TECHNICAL DRAWING





## **ACCESSORY LIST**

AM-X-APA - Surface-mounted adapter AM/AX

## RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
AMWA003SC	<b>₹</b>	SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
AMWA003SC- AZ	<b>□</b> →	SelfControl (SC)	Single battery	RAL 7016	€	no	high	no	unlimited	itself

As of: 14.05.2025 - Subject to technical changes and errors.