



Art.-Nr: AMWA403WL Exit sign Self-contained Wall construction flag, Wireless Professional (WL), 3 h, 22 m, IP40, Zinc die-cast, White

Modern zinc die-cast emergency exit sign luminaire for surface mounting on the wall. Thanks to the wall bracket, the escape and emergency routes are identified at right angles to the wall. This can be done on either one or two sides.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.







More information www.rp-group.com/en/item/AMWA403WL



TECHNICAL DATA

Luminaire type	Exit sign		
Mounting	Wall construction flag		
Recognition distance	22 m		
Pictograph	Set		
Illuminant	LED		
Housing material	Zinc die-cast		
Housing color	White		
Protection type (IP)	IP40		
Impact resistance (IK)	≥ 3		
Certification	WEEE, CE, 5 years warranty		
Insulation class	2		
Supply	Self-contained		
Monitoring	Wireless Professional (WL)		
Bridging time	3 h		
Battery	LiFePO4 6,4 V/1,2 Ah		
Operating mode	Non-maintained / maintained		
Input voltageAC	230 V		







Input frequency	50 Hz			
Power max.	4,7 W			
Power maintained	3,5 W			
Power non-maintained	0,8 W			
Ambient temperature maintained mode	-5 °C to 40 °C			
Ambient temperature non-maintained mode	-5 °C to 40 °C			
Depth	80 mm			
Width	334 mm			
Height	196 mm			
Weight	1.63			
Weight incl. packaging	1.99			
Connection cross-section	2.5 mm²			
Switching input	Yes			
Emergency light blocking	Yes			
Battery connection	Connector			
Dimming function	Yes			
Customs tariff number	94056180			
EAN	4260682153418			





TECHNICAL DRAWING





ACCESSORY LIST

AM-X-APA - Surface-mounted adapter AM/AX LFP3212.K-SET-2AKKU - Battery

RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
AMWA403WL- AZ		Wireless Pro- fessional (WL)	Single battery	RAL 7016	€€	yes	low	yes	1,000 per system	central
AMWA403WL- E	□ →	Wireless Pro- fessional (WL)	Single battery	Edelstahl	€€	yes	low	yes	1,000 per system	central

As of: 16.04.2025 - Subject to technical changes and errors.