



Art.-Nr: ASMU519CC Exit sign Centralised power supply systems Universal, CoreCompact 24 (CC), CPS, 22 m, IP40, Aluminium, Anodised aluminium

Multi-functional aluminium emergency exit sign luminaire for universal mounting. As a result of the clever structure, the recesses for cable entry and fastening are integrated, both for ceiling and wall mounting. Visually appealing side parts cover the lock mechanism so that the luminaire conveys a harmonious and fully closed impression.

Control and monitoring via central 24 V low-power system. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.





More information www.rp-group.com/en/item/ASMU519CC



TECHNICAL DATA


Luminaire type	Exit sign
Mounting	Universal
Recognition distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Aluminium
Housing color	Anodised aluminium
Protection type (IP)	IP40
Impact resistance (IK)	3
Certification	WEEE, CE
Insulation class	3
Supply	Centralised power supply systems
Monitoring	CoreCompact 24 (CC)
Bridging time	CPS
Battery	/
Operating mode	Standby circuit / permanent circuit
Input voltageAC	24 V






2,1 W				
2,1 W				
),4 W				
5 °C to 40 °C				
-5 °C to 40 °C				
4 mm				
.77 mm				
84 mm				
7.75				
.92				
2.5 mm²				
No				
No				
No				
r'es				
4056180				
),, 5 5 5 8)				

TECHNICAL DRAWING





ACCESSORY LIST

DSA - Wire suspension

2PS-EB - Pendant





RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
ASMU019ML	₹	Central power supply (ML)	Central power supply	Alu eloxiert	€€€	Yes	low	Yes	1,920 per system	central
ASMU019ML- WS	1 -	Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central

As of: 04.02.2025 - Subject to technical changes and errors.