

## Exit Sign ceiling-pendulum, SB + SC/8h, pictoset

The AXDP is a zinc-diecast exit sign with pendant fitting for ceiling mounting and for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaires of the A-Series are equipped with modern LED illuminants and offer flexibility with changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838



### Technical data

Luminaire type	Exit sign	Ambient temperature non-maintained mode	-5 °C / 40 °C
Mounting	Ceiling	Length	80 mm
Viewing distance	30 m	Width	312 mm
Pictograph	Set	Height	228 mm
Illuminant	LED	Diameter	
Housing material	Zinc die-cast	Install. dim. length	
Colour	RAL 7016	Install. dim. width	
Mechanical rating IP	40	Install. dim. height	
Impact resistance IK		Install. dim. diameter	
Protection class	2	Weight	2.03 kg
Supply	Self-Contained	Weight incl. Packaging	2.52 kg
Monitoring	Self-Control	Connection cross-section	2.5 mm
Operation time	8 h	Switching input L'	Yes
Battery	4,8V/2,0Ah NiMH	Emergency light blocking	Yes
Operation mode	maintained/non-maintained mode	Battery connector	Plug
Input Voltage AC	230 V	Dimming function	Yes
Input Frequency Hz	50 / 60 Hz	Luminous flux mains mode	
Input Voltage DC	- V	Luminous flux emergency mode	
Power consumption max.	5,6 W		
Power consumption maintained	3,2 W	Customs tariff number	94056080
Power consumption non-maintained	0,35 W	Country of origin	Deutschland
Ambient temperature maintained mode	-5 °C / 40 °C	EAN	

State of: 06 / 2019