



Art.-Nr: AXDP408WL Exit sign Self-contained Pendulum ceiling construction, Wireless Professional (WL), 8 h, 30 m, IP40, Zinc die-cast, White

Modern zinc die-cast emergency exit sign luminaire with pendant for surface mounting on the ceiling. Escape and emergency routes can be identified on either one or two sides.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



More information www.rp-group.com/en/item/AXDP408WL



TECHNICAL DATA

CE

Luminaire type	Exit sign
Mounting	Pendulum ceiling construction
Recognition distance	30 m
Pictograph	Set
Illuminant	LED
Housing material	Zinc die-cast
Housing color	White
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, 5 years warranty
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	8 h
Battery	LiFePO4 6,4 V/1,2 Ah
Operating mode	Non-maintained / maintained
Input voltageAC	230 V







Input frequency	50 Hz
Power max.	5,6 W
Power maintained	4,5 W
Power non-maintained	0,8 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	80 mm
Width	312 mm
Height	228 mm
Weight	2.06
Weight incl. packaging	2.55
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Customs tariff number	94056180
EAN	4260682153845






TECHNICAL DRAWING







ACCESSORY LIST

AM-X-PKG-AZ -AM-X-APA - Surface-mounted adapter AM/AX LFP3212.K-SET-2AKKU - Battery





RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
AXDP408WL- AZ		Wireless Pro- fessional (WL)	Single battery	RAL 7016	€€	yes	low	yes	1,000 per sys- tem	central
AXDP408WL-E		Wireless Pro- fessional (WL)	Single battery	Edelstahl	€€	yes	low	yes	1,000 per sys- tem	central

As of: 16.04.2025 - Subject to technical changes and errors.