RP GROUP
SOLUTIONS IN SAFETY + LIGHTING

Exit sign
Art.-No.: AXR009ML-E

The AXR is a zinc-diecast exit sign for recessed wall mounting and for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaires of the A-Series are equipped with modern LED illuminants and offer flexibility with changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838

TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Recessed wall
Viewing distance	30 m
Pictograph	Set
Illuminant	LED
Housing material	Zinc die-cast
Colour	Stainless steel look
Mechanical rating IP	40
Impact resistance IK	≥ 3
Protection class	2
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	single luminaire switching
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	216 V
Power consumption max.	4,5 W
Power consumption maintained	4,5 W
Power consumption non-maintained	1,1 W
Ambient temperature maintained mode	-20 °C / 40 °C
Ambient temperature non-maintained mode	-20 °C / 40 °C
Length	80 mm
Width	312 mm

Height	238 mm
Install. dim. length	176 mm
Install. dim. width	68 mm
Install. dim. height	40 mm
Weight	1.38 kg
Weight incl. Packaging	1.87 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	None
Dimming function	Yes
Customs tariff number	94056180
Coutry of origin	Germany
EAN	4260581716202

TECHNICAL DRAWING



ACCESSORIES

BALLPLX-AX - Ball protection 440x300x88mm incl. fastening

AM-XBE - A-Serie SB - concrete recessed housing