



#### Art.-Nr: AXRA408WL-E Exit sign Self-contained Wall-mounted flag, Wireless Professional (WL), 8 h, 30 m, IP40, Zinc die-cast, Stainless steel

Modern zinc die-cast emergency exit sign luminaire for recessed mounting in the wall. Thanks to the wall bracket, the escape and emergency routes are identified at right angles to the wall. This can be done on either one or two sides.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.







More information www.rp-group.com/en/item/AXRA408WL-E



#### **TECHNICAL DATA**

| Luminaire type         | Exit sign                   |  |  |  |  |
|------------------------|-----------------------------|--|--|--|--|
| Mounting               | Wall-mounted flag           |  |  |  |  |
| Recognition distance   | 30 m                        |  |  |  |  |
| Pictograph             | Set                         |  |  |  |  |
| Illuminant             | LED                         |  |  |  |  |
| Housing material       | Zinc die-cast               |  |  |  |  |
| Housing color          | Stainless steel             |  |  |  |  |
| Protection type (IP)   | IP40                        |  |  |  |  |
| Impact resistance (IK) | ≥ 3                         |  |  |  |  |
| Certification          | WEEE, CE, 5 years warranty  |  |  |  |  |
| Insulation class       | 2                           |  |  |  |  |
| Supply                 | Self-contained              |  |  |  |  |
| Monitoring             | Wireless Professional (WL)  |  |  |  |  |
| Bridging time          | 8 h                         |  |  |  |  |
| Battery                | LiFePO4 6,4 V/1,2 Ah        |  |  |  |  |
| Operating mode         | Non-maintained / maintained |  |  |  |  |






| Input voltageAC                         | 230 V          |
|---|----------------|
| Input frequency                         | 50 Hz          |
| Power max.                              | 5,6 W          |
| Power maintained                        | 4,5 W          |
| Power non-maintained                    | 0,8 W          |
| Ambient temperature maintained mode     | -5 °C to 40 °C |
| Ambient temperature non-maintained mode | -5 °C to 40 °C |
| Depth                                   | 80 mm          |
| Width                                   | 344 mm         |
| Height                                  | 238 mm         |
| Installation length                     | 176 mm         |
| Installation width                      | 68 mm          |
| Installation height                     | 40 mm          |
| Weight                                  | 1.88           |
| Weight incl. packaging                  | 2.37           |
| Connection cross-section                | 2.5 mm²        |
| Switching input                         | Yes            |
| Emergency light blocking                | Yes            |
| Battery connection                      | Connector      |
| Dimming function                        | Yes            |
| Customs tariff number                   | 94056180       |
| EAN                                     | 4260682155122  |





## **TECHNICAL DRAWING**



# ACCESSORY LIST

AM-XBE -

LFPN3212-SET-2AKKU - Battery

## **RELATED PRODUCTS**

| ArtNo.           | Image     | Monitoring                      | Supply         | Color    | Investment | Automatic log | Maintenance<br>level | Remote main-<br>tenance | max. luminai-<br>res | Single luminai-<br>re monitoring |
|------------------|-----------|---------------------------------|----------------|----------|------------|---------------|----------------------|-------------------------|----------------------|----------------------------------|
| AXRA408WL        | <b>*</b>  | Wireless Pro-<br>fessional (WL) | Single battery | RAL 9003 | €€         | yes           | low                  | yes                     | 1,000 per system     | central                          |
| AXRA408WL-<br>AZ | <b>**</b> | Wireless Pro-<br>fessional (WL) | Single battery | RAL 7016 | €€         | yes           | low                  | yes                     | 1,000 per system     | central                          |

As of: 21.05.2025 - Subject to technical changes and errors.