



Art.-Nr: COFL-051201-NW

LED floodlight, SALO series. Housing made from die-cast aluminium for outdoor use, grey, powder-coated. Cover made from toughened glass. Operating unit installed (can be switched). DC compatible.



More information

www.rp-group.com/en/item/COFL-051201-NW



TECHNICAL DATA

Dimensions	
Product dimensions Length	285 mm
Product dimensions Width	235 mm
Product dimensions Height	150 mm
Product weight	2.7 kg
Packaging dimensions	
Packaging dimensions Length	315 mm
Packaging dimensions Width	180 mm
Packaging dimensions Height	270 mm
Weight incl. packaging	2.9 kg
Housing material	
Housing material	Aluminum die-cast
Certification	
Certification	CE
Protection type (IP)	IP65
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	50 °C



Electrical connection	
Connection cross-section	1.5 mm ²
Type of dimming	CASAMBI
System performance	55 W
Rated power	50 W
Input voltage AC	220-240V / 50-60Hz V
power supply	
DC suitability	Yes
Switching cycles	40000 pcs.
Electrical design	with internal control gear, Switchable
Light data	
Light source	LED
Rated luminous flux	4200 lm
Colour rendering index	> 70 Ra
Beam angle	120 °
Color temperature	4200 K
Light color	742
Service life	40000 h, L70
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	45 °C
Mounting	
Mounting	Universal
CASAMBI Products	
Communication type	Bluetooth
Max. transmission power	+4 dBm

As of: 09.08.2024 - Subject to technical changes and errors.