




## Art.-Nr: DOE021WL Emergency light Self-contained Ceiling mounting, Wireless Professional (WL), 1 h, , IP20, Polycarbonate, Transparent

Small LED safety luminaire, for recessed and surface mounting, with great effect. The small dimensions and transparent housing material make completely unobtrusive mounting possible.

This variant is intended for installation in ceilings. The mounting plate/clips, as well as the emergency light technology in a housing with strain relief, are supplied.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional.





More information www.rp-group.com/en/item/D0E021WL



## **TECHNICAL DATA**

Luminaire type	Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	Transparent
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	1 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	- V





Power max.	5,6 W			
Power maintained	5,2 W			
Power non-maintained	3,8 W			
Ambient temperature maintained mode	-5 °C to 40 °C			
Ambient temperature non-maintained mode	-5 °C to 40 °C			
Depth	24 mm			
Width	50 mm			
Height	12 mm			
Installation dimensions Diameter	10.5 mm			
Weight	0.41			
Weight incl. packaging	0.49			
Connection cross-section	1.5 mm²			
Switching input	Yes			
Emergency light blocking	Yes			
Battery connection	Clip			
Dimming function	No			
Luminous flux mains	140 lm			
Luminous flux emergency	140 lm			
Customs tariff number	94056120			
EAN	4260659560881			






## TECHNICAL DRAWING










ø 10,5











DO verschiedene Einbaumaße

## RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
DOE021		Without monitoring		Transparent						
DOE021SC		SelfControl (SC)	Single battery	Transparent	€	no	high	no	unlimited	itself

As of: 17.05.2025 - Subject to technical changes and errors.