



Art.-Nr: ED-073602-NW

LED recessed downlight "CANTONE", round, 68x49mm, 7W, 480lm, 4000K, CRI >80, IP20

Compact design and neutral white light (4000K) with high colour rendering index (CRI >80) for professional lighting.

LED recessed downlights, Cantone series. Four different covers in white, chrome, chrome matt and brushed metal, available in a round/square version. Operating unit can be dimmed (TRIAC/DALI dimmer), external. Version with CASAMBI® Bluetooth control available.



More information

www.rp-group.com/en/item/ED-073602-NW



TECHNICAL DATA

Dimensions	
Product dimensions Length	92 mm
Product dimensions Width	92 mm
Product dimensions Height	50 mm
Product weight	0.18 kg
Packaging dimensions	
Packaging dimensions Length	130 mm
Packaging dimensions Width	100 mm
Packaging dimensions Height	75 mm
Weight incl. packaging	0.28 kg
Cutout Dimensions	
Diameter	68 mm
Installation depth	50 mm
Color	
Color	White
Housing material	
Housing material	Aluminium
Certification	
Certification	CE
Insulation class	2



Protection type (IP)	IP20
Storage temperature range	
Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+50 °C
Electrical connection	
Connection cross-section	1.5 mm ²
Type of dimming	TRIAC, DALI
System performance	8.1 W
Input voltage AC	220-240V / 50-60Hz V
Power factor	0.85 PF
power supply	
DC suitability	Yes
Electrical design	with external control gear, Dimmable
Light data	
Light source	LED
Rated luminous flux	480 lm
Colour rendering index	> 80 Ra
Beam angle	38 °
Color temperature	4000 K
Light color	840
LED manufacturer	Sharp LED
Service life	50000 h, L70
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+45 °C
Mounting	
Mounting	Universal

As of: 14.01.2026 - Subject to technical changes and errors.