

CE



Art.-Nr: ED-073602-WW LED recessed downlight "CANTONE", round, 68x49mm, 7W, 450lm, 2700K, CRI >80, IP20

LED recessed downlights, Cantone series. Four different covers in white, chrome, chrome matt and brushed metal, available in a round/square version. Operating unit can be dimmed (TRIAC/DALI dimmer), external. Version with CASAMBI® Bluetooth control available.



More information www.rp-group.com/en/item/ED-073602-WW



TECHNICAL DAT

Dimensions		
Product dimensions Length	92 mm	
Product dimensions Width	92 mm	
Product dimensions Height	50 mm	
Product weight	0.18 kg	
Packaging dimensions		
Packaging dimensions Length	130 mm	
Packaging dimensions Width	100 mm	
Packaging dimensions Height	75 mm	
Weight incl. packaging	0.28 kg	
Cutout Dimensions		
Diameter	68 mm	
Installation depth	50 mm	
Color		
Color	White	
Housing material		
Housing material	Aluminium	
Certification		
Certification	CE	
Insulation class	2	
Protection type (IP)	IP20	
Storage temperature range		





Storage temperature range (Min)	-25 °C
Storage temperature range (Max)	+50 °C
Electrical connection	
Connection cross-section	1.5 mm²
Type of dimming	TRIAC, DALI
System performance	8.1 W
Input voltage AC	220-240V / 50-60Hz V
Power factor	0.85 PF
power supply	
DC suitability	Yes
Electrical design	with external control gear, Dimmable
Energy efficiency rating	В
Light data	
Light source	LED
Rated luminous flux	450 lm
Colour rendering index	> 80 Ra
Beam angle	38 °
Color temperature	2700 K
Light color	827
LED manufacturer	Sharp LED
Service life	50000 h, L70
Temperatures	
Ambient temperature (Min)	-20 °C
Ambient temperature (Max)	+45 °C
Mounting	
Mounting	Universal

As of: 10.04.2025 - Subject to technical changes and errors.