



Emergency luminaire Art.-No.: FMDS529CC-AZ

Robust ceiling-mounted Zinc die-cast luminaire for the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 605982-22 and EN 1838. Appealing design with concealed screws.
Available for central power systems or as self-contained LED emergency luminaire. HACCP certified.




TECHNICAL DATA

| | |
|---|--------------------------------|
| Luminaire type | Emergency luminaire |
| Mounting | Ceiling mounted |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Zinc die-cast |
| Colour | RAL 7016 |
| Mechanical rating IP | 65 |
| Impact resistance IK | 8 |
| Protection class | 3 |
| Supply | Central power supply system |
| Monitoring | CC - CoreCompact 24V |
| Operation time | CPS |
| Operation mode | maintained/non-maintained mode |
| Input Voltage AC | 24 V |
| Power consumption max. | 3,8 W |
| Power consumption maintained | 3,8 W |
| Power consumption non-maintained | 0,4 W |
| Ambient temperature maintained mode | -5 °C / 40 °C |
| Ambient temperature non-maintained mode | -5 °C / 40 °C |
| Length | 58 mm |
| Width | 262 mm |
| Height | 188 mm |
| Weight | 1.92 kg |
| Weight incl. Packaging | 2.02 kg |
| Connection cross-section | 2.5 mm |



| | |
|------------------------------|---------------|
| Switching input L' | No |
| Emergency light blocking | No |
| Battery connector | None |
| Luminous flux mains mode | 520 lm |
| Luminous flux emergency mode | 520 lm |
| Customs tariff number | 94056180 |
| Coutry of origin | Germany |
| EAN | 4260682157126 |

TECHNICAL DRAWING



ACCESSORIES

- FMDA001-AZ - ceiling bracket, single sided black
- FMDA002-AZ - ceiling bracket, double sided white
- FMWA001 - Surface mounting adapter for lateral cable feed
- FMFH - flexible wall mounting for FM