



Art.-Nr: KCD013WL-IP64
Exit sign Self-contained
Surface mounting, Wireless Professional (WL), 3 h, 30 m,
IP64, Polycarbonate, White

Slim convex plastic emergency exit sign luminaire for ceiling mounting.
Emergency exit sign luminaire with plug-in set of pictograms fitted on the inside without the use of solvents is supplied as standard. In accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

Pre-assembled with eye bolts for suspension.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.



More information

www.rp-group.com/en/item/KCD013WL-IP64



TECHNICAL DATA



Luminaire type	Exit sign
Mounting	Surface mounting
Recognition distance	30 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP64
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, D-Sign
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	3 h
Battery	NIMH 12 V/0,8 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V



Input frequency	50 / 60 Hz
Input voltage DC	- V
Power max.	7,5 W
Power maintained	7,5 W
Power non-maintained	3,6 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	90 mm
Width	340 mm
Height	170 mm
Weight	1.24
Weight incl. packaging	1.37
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	Yes
Luminous flux mains	150 lm
Luminous flux emergency	150 lm
Customs tariff number	94056120
GTIN	4260682147837



TECHNICAL DRAWING



ACCESSORY LIST

KCAWW - Wall bracket

DSA - Wire suspension



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
KCD013-IP64		Without monitoring		RAL 9003						
KCD013SC-IP64		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KCD013WLSE-IP64		Wireless Professional (WL)	Single battery	RAL 9003	€€	yes	low	yes	1,000 per system	central

As of: 05.09.2025 - Subject to technical changes and errors.