



Art.-Nr: KCW019ML-P Emergency light Centralised power supply systems Wall mounting, Central power supply (ML), CPS, 30 m, IP54, Polycarbonate, White

Slightly curved high-grade emergency luminaire in polycarbonate for wall or ceiling mounting.

Emergency luminaire according to EN 60598-1, EN 60598-2-22 and EN 1838 norms.

Control and monitoring via central power supply system. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard.





More information www.rp-group.com/en/item/KCW019ML-P



TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Wall mounting
Recognition distance	30 m
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP54
Impact resistance (IK)	6
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching
Input voltageAC	230 V
Input frequency	50 / 60 Hz






Input voltage DC	216 V			
Power max.	5,2 W			
Power maintained	5,2 W			
Power non-maintained	1,1 W			
Ambient temperature maintained mode	-20 °C to 40 °C			
Ambient temperature non-maintained mode	-20 °C to 40 °C			
Depth	60 mm			
Width	340 mm			
Height	170 mm			
Weight	0.7			
Weight incl. packaging	0.79			
Connection cross-section	2.5 mm²			
Switching input	Yes			
Emergency light blocking	No			
Battery connection	No			
Dimming function	Yes			
Luminous flux mains	300 lm			
Luminous flux emergency	300 lm			
Customs tariff number	94056120			
EAN	4260123681562			





TECHNICAL DRAWING



ACCESSORY LIST

BALL2 - Wire mesh guard

DWKCW -

KC-IP65 -

KCER - Mounting frame

KCWFH - Wall holder





RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
KCW019ML	₩ →	Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central
KCW019ML- COOL	₹	Central power supply (ML)	Central power supply	RAL 9003	€€€	Yes	low	Yes	1,920 per system	central
KCW519CC	₹ →	CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central

As of: 15.04.2025 - Subject to technical changes and errors.