



Art.-Nr: KCW029ML-IP65
Emergency light Centralised power supply systems
Universal, Central power supply (ML), CPS, 30 m, IP65,
Polycarbonate, White

Slim convex luminaire out of of polycarbonate.

As safety luminaire for escape route lighting with a clear cover preferably for ceiling mounting.

Control and monitoring via central power supply system. The luminaire is fitted with the innovative flexible plug-in system for rapid use of the right lens. The hall lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information

www.rp-group.com/en/item/KCW029ML-IP65





TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Universal
Recognition distance	30 m
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	WEEE, CE, D-Sign
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Central power supply (ML)
Bridging time	CPS
Battery	/
Operating mode	single luminaire switching
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V



Power max.	5,2 W
Power maintained	5,2 W
Power non-maintained	1,1 W
Ambient temperature maintained mode	-20 °C to 40 °C
Ambient temperature non-maintained mode	-20 °C to 40 °C
Depth	60 mm
Width	340 mm
Height	170 mm
Weight	0.72
Weight incl. packaging	0.81
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056120
EAN	4260349829298

TECHNICAL DRAWING





ACCESSORY LIST

BALL2 - Wire mesh guard

DWKCW -

KC-IP65 -

KCER - Mounting frame

KCWFH - Wall holder

As of: 15.04.2025 - Subject to technical changes and errors.