



Art.-Nr: KMB011WB Emergency light Self-contained Universal, Wireless Basic (WB), 1 h, , IP54, Polycarbonate, White

Compact safety luminaire for universal mounting. The narrow rectangular plastic housing is discreetly reduced to the essentials. Illumination of the escape and emergency routes is assisted by the optics integrated in the surround.

Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.

Wireless control and monitoring for small installations of up to 50 luminaires with Wireless Basic. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame





More information www.rp-group.com/en/item/KMB011WB



TECHNICAL DATA


Luminaire type	Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP54
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	Wireless Basic (WB)
Bridging time	1 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltageAC	230 V
Input frequency	50 / 60 Hz






Input voltage DC	- V			
Power max.	5,3 W			
Power maintained	3,9 W			
Power non-maintained	1,5 W			
Ambient temperature maintained mode	-10 °C to 40 °C			
Ambient temperature non-maintained mode	-5 °C to 40 °C			
Depth	250 mm			
Width	34 mm			
Height	50 mm			
Weight	0.58			
Weight incl. packaging	0.65			
Connection cross-section	2.5 mm²			
Switching input	Yes			
Emergency light blocking	No			
Battery connection	Connector			
Dimming function	No			
Luminous flux mains	190 lm			
Luminous flux emergency	190 lm			
Customs tariff number	94056120			
EAN	4260581712303			

TECHNICAL DRAWING







ACCESSORY LIST

KME-EB - Mounting frame

BALL1 - Wire mesh guard

KMBE - Concrete-mounted box

BALLPLX-KMB - Wire mesh surround

KMBFH -





RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
KMB011SC		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KMB011SC- G10		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KMB011WL	4	Wireless Pro- fessional (WL)	Single battery	RAL 9003	€€	yes	low	yes	1,000 per system	central
KMB011WL- G10		Wireless Pro- fessional (WL)	Single battery	RAL 9003	€€	yes	low	yes	1,000 per system	central

As of: 15.04.2025 - Subject to technical changes and errors.