



### Art.-Nr: KMB019ML Safety luminaire Centralised power supply systems Universal, Central power supply (ML), CPS, , IP54, Plastic, white

Compact safety luminaire for universal mounting. The narrow rectangular plastic housing is discreetly reduced to the essentials. Illumination of the escape and emergency routes is assisted by the optics integrated in the surround.

Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.

Control and monitoring via central power supply system. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.









More information www.rp-group.com/en/item/KMB019ML



#### **TECHNICAL DATA**


Luminaire type	Safety luminaire				
Mounting	Universal				
Pictograph	No				
Illuminant	LED				
Housing material	Plastic				
Housing color	white				
Protection type (IP)	IP54				
Impact resistance (IK)	≥ 3				
Certification	WEEE, CE, TÜV Rheinland Type approved, ENEC				
Insulation class	2				
Supply	Centralised power supply systems				
Monitoring	Central power supply (ML)				
Bridging time	CPS				
Battery	/				
Operating mode	single luminaire switching				
Input voltageAC	230 V				
Input frequency	50 / 60 Hz				
Input voltage DC	216 V				






Power max.	3,2 W
Power maintained	3,2 W
Power non-maintained	1 W
Ambient temperature maintained mode	-30 °C to 40 °C
Ambient temperature non-maintained mode	-30 °C to 40 °C
Depth	250 mm
Width	34 mm
Height	50 mm
Weight	0.5
Weight incl. packaging	0.57
Connection cross-section	1.5 mm²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	200 lm
Luminous flux emergency	200 lm
Customs tariff number	94056120
EAN	4260123690090

### **TECHNICAL DRAWING**







# ACCESSORY LIST

KME-EB - Mounting frame

BALL1 - Wire mesh guard

KMBE - Concrete-mounted box

BALLPLX-KMB - Wire mesh surround

KMBFH -





# RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
KMB019ML- SW		Central power supply (ML)	Central power supply	RAL 9005	€€€	Yes	low	Yes	1,920 per system	central
KMB519CC		CoreCompact 24 (CC)	Central power supply	RAL 9003	€€	Yes	low	Yes		central

As of: 05.02.2025 - Subject to technical changes and errors.