



**Art.-Nr: KMU013WL-3P**  
**Exit sign Self-contained**  
**3-phase conductor rail, Wireless Professional (WL), 3 h, 24 m, IP43, Polycarbonate, White**

Slim convex emergency exit sign luminaire with 3-phase adapter. Planning certainty for identifying escape and emergency routes for inscription on one or two sides is provided by tool-free variable use of the pictograms on site. The pictograms are inserted without the use of solvents. The set of pictograms (arrow to the right, left, up or down) is supplied as standard.

The pre-mounted 3-phase adapter allows for tool-free installation in popular 3-phase tracks, such as Nordic Aluminium GLOBAL pro (previously NOKIA) XTS, XTTS and XTSC.

Emergency exit sign luminaire in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.



More information  
[www.rp-group.com/en/item/KMU013WL-3P](http://www.rp-group.com/en/item/KMU013WL-3P)



## TECHNICAL DATA


Luminaire type	Exit sign
Mounting	3-phase conductor rail
Recognition distance	24 m
Pictograph	Set
Illuminant	LED
Housing material	Polycarbonate
Housing color	White
Protection type (IP)	IP43
Impact resistance (IK)	3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained



Monitoring	Wireless Professional (WL)
Bridging time	3 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	- V
Power max.	5,3 W
Power maintained	3,9 W
Power non-maintained	1,5 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	34 mm
Width	250 mm
Height	174 mm
Weight	0.45
Weight incl. packaging	0.62
Connection cross-section	2.5 mm <sup>2</sup>
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	190 lm
Luminous flux emergency	190 lm
Customs tariff number	94056120
EAN	4260682152213



## TECHNICAL DRAWING



## ACCESSORY LIST

LFP3233.01 - Battery



## RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
KMU003SC-3P		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KMU003SC-SW-3P		SelfControl (SC)	Single battery	RAL 9005	€	no	high	no	unlimited	itself
KMU013SC-3P		SelfControl (SC)	Single battery	RAL 9003	€	no	high	no	unlimited	itself
KMU013SC-SW-3P		SelfControl (SC)	Single battery	RAL 9005	€	no	high	no	unlimited	itself
KMU013WL-SW-3P		Wireless Professional (WL)	Single battery	RAL 9005	€€	yes	low	yes	1,000 per system	central

As of: 27.05.2025 - Subject to technical changes and errors.