



Art.-Nr: KMU411WL-SW
Exit sign Self-contained
Universal, Wireless Professional (WL), 1 h, 24 m, IP43,
Polycarbonate, Black

Slim, convex plastic luminaire for universal mounting and identifying escape and emergency routes for inscription on one or two sides in accordance with DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838. LED technology with white high-power SMD LEDs.

Housing colour: RAL 9005 black

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. Universal mounting includes fitting on the wall and ceiling as well as the option of fitting in the ceiling in conjunction with the mounting frame available.



More information

www.rp-group.com/en/item/KMU411WL-SW



TECHNICAL DATA


| | |
|------------------------|-----------------------------|
| Luminaire type | Exit sign |
| Mounting | Universal |
| Recognition distance | 24 m |
| Pictograph | Set |
| Illuminant | LED |
| Housing material | Polycarbonate |
| Housing color | Black |
| Protection type (IP) | IP43 |
| Impact resistance (IK) | 3 |
| Certification | WEEE, CE, 5 years warranty |
| Insulation class | 2 |
| Supply | Self-contained |
| Monitoring | Wireless Professional (WL) |
| Bridging time | 1 h |
| Battery | LiFePO4 3,2 V/1,6 Ah |
| Operating mode | Non-maintained / maintained |



| | |
|---|---------------------|
| Input voltage AC | 230 V |
| Input frequency | 50 / 60 Hz |
| Input voltage DC | - V |
| Power max. | 5,3 W |
| Power maintained | 3,9 W |
| Power non-maintained | 1,5 W |
| Ambient temperature maintained mode | -5 °C to 35 °C |
| Ambient temperature non-maintained mode | -5 °C to 35 °C |
| Depth | 34 mm |
| Width | 250 mm |
| Height | 174 mm |
| Weight | 0.42 |
| Weight incl. packaging | 0.52 |
| Connection cross-section | 2.5 mm ² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | Connector |
| Dimming function | No |
| Luminous flux mains | 190 lm |
| Luminous flux emergency | 190 lm |
| Customs tariff number | 94056120 |
| EAN | 4260766559969 |



TECHNICAL DRAWING



ACCESSORY LIST

- DSA - Wire suspension
- 2PSW-EB -
- KME-SW - Mounting frame
- AWKSU - Wall bracket
- KMBE - Concrete-mounted box
- BALLPLX-KMU - Wire mesh surround

As of: 20.03.2025 - Subject to technical changes and errors.