




Art.-Nr: LFU15009ML-CCT

LED diffuser, VASCA series. Polycarbonate housing. Prismatic diffuser made of UV-resistant PC. The diffuser is attached with stainless steel clips. The LED circuit board is individually replaceable. The luminaire also features through-wiring.

The wattage (36 - 55W / 4400 - 7700lm) and color temperature (3000 - 4000 - 5000K) are individually adjustable via DIP switches.

Control and monitoring via central power supply system.



More information

www.rp-group.com/en/item/LFU15009ML-CCT




TECHNICAL DATA

Luminaire type	Emergency light, General light
Mounting	Wall mounting, Surface mounting
Pictograph	No
Housing material	Polycarbonate
Housing color	Light grey
Protection type (IP)	IP66
Impact resistance (IK)	8
Certification	CE, WEEE
Insulation class	1
Monitoring	Central power supply (ML)
Battery	/
Ambient temperature maintained mode	-20 °C to 40 °C
Ambient temperature non-maintained mode	-20 °C to 40 °C
Depth	1560 mm
Width	82 mm
Height	97 mm
Weight	2.2
Weight incl. packaging	2.55
Customs tariff number	94051140
GTIN	4262483029756



TECHNICAL DRAWING



As of: 07.10.2025 - Subject to technical changes and errors.