



## Exit sign Art.-No.: LSW011WL

Emergency luminaire in a sleek Aluminium profile, matt anodized for wall mounting with an additional light source to light the Floor below the luminaire. Housing is openable toollessly. Applicable for maintained or non-maintained operation. The toolless Change and variable use of these pictograms provide planning security on site. Pluggable set of pictograms (left, right, down, up) is included in the scope of delivery. Emergency luminaire according to DIN EN 60598-1, DIN EN 60598-2-22 und DIN EN 1838.



### TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Wall mounted
Viewing distance	56 m
Pictograph	acc. to Specification
Illuminant	LED
Housing material	Aluminium
Colour	Alu anodized
Mechanical rating IP	40
Impact resistance IK	≥ 3
Protection class	1
Supply	Single battery
Monitoring	WL - Wireless Professional
Operation time	1 h
Battery	12V/0,8Ah NiMH
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	- V
Power consumption max.	7,5 W
Power consumption maintained	7,5 W
Power consumption non-maintained	3,6 W
Ambient temperature maintained mode	-5 °C / 40 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	62 mm



Width	614 mm
Height	334 mm
Weight	3.15 kg
Weight incl. Packaging	3.15 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	Clamp
Dimming function	Yes
Luminous flux mains mode	150 lm
Luminous flux emergency mode	150 lm
Customs tariff number	94056180
Country of origin	Germany
EAN	4260659562687

## TECHNICAL DRAWING

