



**Art.-Nr: PFW019ML**

**Exit sign Centralised power supply systems**

**Wall mounting, Central power supply (ML), CPS, 24 m, IP65, Plastic, white**

Robust plastic emergency exit sign or safety luminaire.

Use as an emergency exit sign luminaire for wall mounting.

Or without the use of pictograms as a safety luminaire with the prismatic cover included, preferably for ceiling mounting.

Control and monitoring via **central power supply system**. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (arrow to the right, left, up and down) is supplied as standard. The luminaire is fitted with the innovative **flexible plug-in system** for rapid use of the right lens. The hall lens is supplied with every luminaire. A round lens, spotlight lens and beam lens are available as options.



More information

[www.rp-group.com/en/item/PFW019ML](http://www.rp-group.com/en/item/PFW019ML)



## TECHNICAL DATA

|                        |   |
|------------------------|---|
| Luminaire type         | Exit sign   |
| Mounting               | Wall mounting                                       |
| Recognition distance   | 24 m  |
| Pictograph             | Set   |
| Illuminant             | LED   |
| Housing material       | Plastic   |
| Housing color          | white   |
| Protection type (IP)   | IP65  |
| Impact resistance (IK) | 5   |
| Certification          | WEEE, CE, ENEC, D-Sign, TÜV Rheinland Type approved |
| Insulation class       | 1   |
| Supply                 | Centralised power supply systems                    |
| Monitoring             | Central power supply (ML)                           |
| Bridging time          | CPS   |
| Battery                | /   |
| Operating mode         | single luminaire switching                          |



|                          |                     |
|--------------------------|---------------------|
| Input voltageAC          | 230 V               |
| Input frequency          | 50 / 60 Hz          |
| Input voltage DC         | 216 V               |
| Power max.               | 5,2 W               |
| Power DS                 | 5,2 W               |
| Power BS                 | 1,1 W               |
| Ambient temperature DS   | -20 °C to 40 °C     |
| Ambient temperature BS   | -20 °C to 40 °C     |
| Depth                    | 370 mm              |
| Width                    | 105 mm              |
| Height                   | 152 mm              |
| Weight                   | 0.95                |
| Weight incl. packaging   | 1.08                |
| Connection cross-section | 2.5 mm <sup>2</sup> |
| Switching input          | Yes                 |
| Emergency light blocking | No                  |
| Battery connection       | No                  |
| Dimming function         | Yes                 |
| Luminous flux mains      | 300 lm              |
| Luminous flux emergency  | 300 lm              |
| Customs tariff number    | 94056120            |
| EAN                      | 4260123683818       |



## TECHNICAL DRAWING



## ACCESSORY LIST

BALL2 - Wire mesh guard



## RELATED PRODUCTS

| Art.-No.   | Image   | Monitoring                | Supply               | Color    | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires  | Single luminaire monitoring |
|------------|---|---------------------------|----------------------|----------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| PFW019ML-P |  | Central power supply (ML) | Central power supply | RAL 9003 | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |
| PFW519CC   |  | CoreCompact 24 (CC)       | Central power supply | RAL 9003 | €€         | Yes           | low               | Yes                |                  | central                     |
| PFW519CC-P |  | CoreCompact 24 (CC)       | Central power supply | RAL 9003 | €€         | Yes           | low               | Yes                |                  | central                     |

As of: 03.01.2025 - Subject to technical changes and errors.