



**Art.-Nr: PXWK403SC**

**Exit sign Self-contained**

**Wall mounting, SelfControl (SC), 3 h, 30 m, IP65, PCABS, Polycarbonate, White**

Polycarbonate LED emergency exit sign luminaire with convex shaped surround for wall mounting. To help with mounting, levelling screws are integrated to compensate for uneven surfaces. The set of pictograms is inserted on the inside and secured without the use of solvents.



Automatic monitoring of safety luminaire with SelfControl. Planning certainty is provided by tool-free, variable use of the pictograms on site. A set of pictograms corresponding to DIN ISO 7010 (2x man in the door and 2 straight arrows) are supplied as standard.



More information

[www.rp-group.com/en/item/PXWK403SC](http://www.rp-group.com/en/item/PXWK403SC)



## TECHNICAL DATA


|                        |                             |
|------------------------|-----------------------------|
| Luminaire type         | Exit sign                   |
| Mounting               | Wall mounting               |
| Recognition distance   | 30 m                        |
| Pictograph             | Set                         |
| Illuminant             | LED                         |
| Housing material       | PCABS, Polycarbonate        |
| Housing color          | White                       |
| Protection type (IP)   | IP65                        |
| Impact resistance (IK) | 5                           |
| Certification          | CE, WEEE                    |
| Insulation class       | 2                           |
| Supply                 | Self-contained              |
| Monitoring             | SelfControl (SC)            |
| Bridging time          | 3 h                         |
| Battery                | LiFePO4 3,2 V/1,6 Ah        |
| Operating mode         | Non-maintained / maintained |
| Power max.             | 3,8 W                       |
| Power maintained       | 2,3 W                       |



|   |                     |
|---|---------------------|
| Power non-maintained                    | 0,3 W               |
| Ambient temperature maintained mode     | 0 °C to 40 °C       |
| Ambient temperature non-maintained mode | 0 °C to 40 °C       |
| Depth                                   | 68 mm               |
| Width                                   | 320 mm              |
| Height                                  | 168 mm              |
| Weight                                  | 0.84                |
| Weight incl. packaging                  | 0.93                |
| Connection cross-section                | 1,5 mm <sup>2</sup> |
| Switching input                         | Yes                 |
| Emergency light blocking                | No                  |
| Battery connection                      | Connector           |
| Dimming function                        | No                  |
| Luminous flux mains                     | 140 lm              |
| Luminous flux emergency                 | 140 lm              |
| Customs tariff number                   | 94056120            |
| GTIN                                    | 4262483025758       |



## TECHNICAL DRAWING



## ACCESSORY LIST

PXD-PIKTOSETSONDER.01 - Pictogram set for marking accessible escape routes

As of: 12.01.2026 - Subject to technical changes and errors.