



Combined emergency luminaire Art.-No.: QAW009-SIWW-BM

Round metal luminaire for general lighting and the lighting of escape and rescue route according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838.

This luminaire is designed for use with central battery systems. The LED-luminaire is operated with 26W, 1.600lm and light colour 4000 Kelvin. On mains failure the central battery system continues the supply of the emergency luminaire. On mains operation or failure the luminaire, supplied by the central battery system, operates at 100% luminous flux.



TECHNICAL DATA

| | |
|---|--------------------------------|
| Luminaire type | Combined emergency luminaire |
| Mounting | Universal |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Aluminium |
| Colour | Alu anodized |
| Mechanical rating IP | 20 |
| Impact resistance IK | ≥ 3 |
| Protection class | 1 |
| Supply | Central power supply system |
| Monitoring | None |
| Operation time | CPS |
| Operation mode | maintained/non-maintained mode |
| Input Voltage AC | 230 V |
| Input Frequency Hz | 50 Hz |
| Input Voltage DC | 216 V |
| Power consumption max. | 26 W |
| Power consumption maintained | 26 W |
| Power consumption non-maintained | 0 W |
| Ambient temperature maintained mode | -20 °C / 30 °C |
| Ambient temperature non-maintained mode | -20 °C / 40 °C |
| Height | 113 mm |
| Diameter | 395 mm |
| Weight | 0.75 kg |



| | |
|------------------------------|---------------|
| Weight incl. Packaging | 1.07 kg |
| Connection cross-section | 1.5 mm |
| Switching input L' | No |
| Emergency light blocking | No |
| Battery connector | None |
| Dimming function | No |
| Luminous flux mains mode | 2300 lm |
| Luminous flux emergency mode | 2300 lm |
| Customs tariff number | 94056120 |
| Country of origin | Germany |
| EAN | 4260659563417 |

TECHNICAL DRAWING

