



## Combined emergency luminaire Art.-No.: QAW009ML-SI-BM

Round metal luminaire for general lighting and the lighting of escape and rescue route according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838.

This luminaire is designed for use with central battery systems. The LED-luminaire is operated with 26W, 1.600lm and light colour 4000 Kelvin. On mains failure the central battery system continues the supply of the emergency luminaire. On mains operation or failure the luminaire, supplied by the central battery system, operates at 100% luminous flux. This luminaire is equipped with a motion sensor.



### TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminium
Colour	Alu anodized
Mechanical rating IP	20
Impact resistance IK	≥ 3
Protection class	1
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 Hz
Input Voltage DC	216 V
Power consumption max.	26 W
Power consumption maintained	26 W
Power consumption non-maintained	0 W
Ambient temperature maintained mode	-20 °C / 30 °C
Ambient temperature non-maintained mode	-20 °C / 40 °C
Height	113 mm
Diameter	395 mm



Weight	0.75 kg
Weight incl. Packaging	1.07 kg
Connection cross-section	1.5 mm
Switching input L'	No
Emergency light blocking	No
Battery connector	None
Dimming function	No
Luminous flux mains mode	2300 lm
Luminous flux emergency mode	2300 lm
Customs tariff number	94056180
Coutry of origin	Germany
EAN	4260659563370

## TECHNICAL DRAWING

