



Combined emergency luminaire Art.-No.: QAW029ML-BMWW

Round metal luminaire for general lighting and illumination of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838.

There is an integrated emergency light inside the luminaire, which is supplied by the central battery system. In mains operation, the general light with 26W, 2,300lm, 3000 Kelvin is switched via the integrated motion detector.



TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminium
Colour	RAL 9003
Mechanical rating IP	20
Impact resistance IK	≥ 3
Protection class	1
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	single luminaire switching
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	216 V
Power consumption max.	30,6 W
Power consumption maintained	27,2 W
Power consumption non-maintained	1,2 W
Ambient temperature maintained mode	-20 °C / 30 °C
Ambient temperature non-maintained mode	-20 °C / 40 °C
Height	113 mm
Diameter	395 mm
Weight	0.7 kg



Weight incl. Packaging	1.02 kg
Connection cross-section	2.5 mm
Switching input L'	No
Emergency light blocking	No
Battery connector	None
Dimming function	Yes
Luminous flux mains mode	2300 lm
Luminous flux emergency mode	360 lm
Customs tariff number	94056180
Country of origin	Germany
EAN	4260659563486

TECHNICAL DRAWING

