



Art.-Nr: QAW403SC-SI-BM
General light, Emergency light Self-contained
Universal, SelfControl (SC), 3 h , IP20, Aluminium, White

Round aluminium LED luminaire, general-purpose luminaire with integrated safety light function for illuminating escape and emergency routes.

Automatic monitoring of safety luminaire with SelfControl. Our motion detector (BM) reliably detects movements and automatically turns on the light in mains operation.



More information

www.rp-group.com/en/item/QAW403SC-SI-BM



TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminium
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, 5 years warranty
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 3,2 V/4,5 Ah
Operating mode	Non-maintained / maintained
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Power max.	30 W
Power maintained	28 W



Power non-maintained	2 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Height	113 mm
Diameter	395 mm
Weight	0.787
Weight incl. packaging	1.107
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	2300 lm
Luminous flux emergency	360 lm
Customs tariff number	94056180
EAN	4260682159694



TECHNICAL DRAWING



As of: 29.04.2025 - Subject to technical changes and errors.