



Art.-Nr: QAW423WB-SI
General light, Emergency light Self-contained
Universal, Wireless Basic (WB), 3 h, , IP20, Aluminium,
Anodised aluminium

Round aluminium LED luminaire, general-purpose luminaire with integrated safety light function for illuminating escape and emergency routes.

Wireless control and monitoring for small installations of up to 50 luminaires with Wireless Basic.



More information
www.rp-group.com/en/item/QAW423WB-SI



TECHNICAL DATA

| | |
|------------------------|--------------------------------|
| Luminaire type | General light, Emergency light |
| Mounting | Universal |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Aluminium |
| Housing color | Anodised aluminium |
| Protection type (IP) | IP20 |
| Impact resistance (IK) | ≥ 3 |
| Certification | WEEE, CE, 5 years warranty |
| Insulation class | 1 |
| Supply | Self-contained |
| Monitoring | Wireless Basic (WB) |
| Bridging time | 3 h |
| Battery | LiFePO4 3,2 V/3,3 Ah |
| Operating mode | Non-maintained / maintained |
| Input voltageAC | 230 V |
| Input frequency | 50 / 60 Hz |
| Power max. | 30 W |
| Power maintained | 26,4 W |



| | |
|---|---------------------|
| Power non-maintained | 0,4 W |
| Ambient temperature maintained mode | -5 °C to 30 °C |
| Ambient temperature non-maintained mode | -5 °C to 35 °C |
| Height | 113 mm |
| Diameter | 395 mm |
| Weight | 0.78 |
| Weight incl. packaging | 1.1 |
| Connection cross-section | 2.5 mm ² |
| Switching input | Yes |
| Emergency light blocking | No |
| Battery connection | Connector |
| Dimming function | Yes |
| Luminous flux mains | 2300 lm |
| Luminous flux emergency | 250 lm |
| Customs tariff number | 94056180 |
| EAN | 4262483024218 |



TECHNICAL DRAWING



As of: 29.04.2025 - Subject to technical changes and errors.