



**Art.-Nr: QAW423WL-BM**  
**General light, Emergency light Self-contained**  
**Universal, Wireless Professional (WL), 3 h, , IP20, Aluminium,**  
**White**

Round metal luminaire for general lighting and the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. In mains operation the luminaire works with 26W / 2.300lm LED. The general light is switched independently of the emergency light via the motion detector, which is not visible from the outside.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. Our motion detector (**BM**) reliably detects movements and automatically turns on the light in mains operation.



More information  
[www.rp-group.com/en/item/QAW423WL-BM](http://www.rp-group.com/en/item/QAW423WL-BM)



## TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminium
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE, 5 years warranty
Insulation class	1
Supply	Self-contained
Monitoring	Wireless Professional (WL)
Bridging time	3 h
Battery	LiFePO4 3,2 V/3,3 Ah
Operating mode	Non-maintained / maintained
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Power max.	30 W



Power maintained	26,4 W
Power non-maintained	0,4 W
Ambient temperature maintained mode	-5 °C to 30 °C
Ambient temperature non-maintained mode	-5 °C to 35 °C
Height	113 mm
Diameter	395 mm
Weight	0.78
Weight incl. packaging	1.1
Connection cross-section	2.5 mm <sup>2</sup>
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	2300 lm
Luminous flux emergency	250 lm
Customs tariff number	94056180
EAN	4260682159892



## TECHNICAL DRAWING



As of: 29.04.2025 - Subject to technical changes and errors.