



Combined emergency luminaire Art.-No.: QAW428WL-WW

Round metal luminaire for general lighting and the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. The LED-luminaire is operated with 26W, 2.300lm and light colour 3000 Kelvin.



TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminium
Colour	RAL 9003
Mechanical rating IP	20
Impact resistance IK	≥ 3
Protection class	1
Supply	Single battery
Monitoring	WL - Wireless Professional
Operation time	8 h
Battery	3.2V / 3.3 Ah LiFePO4
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Power consumption max.	30 W
Power consumption maintained	26,4 W
Power consumption non-maintained	0,4 W
Ambient temperature maintained mode	-5 °C / 30 °C
Ambient temperature non-maintained mode	-5 °C / 35 °C
Height	113 mm
Diameter	395 mm
Weight	0.78 kg



Weight incl. Packaging	1.1 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	Plug
Dimming function	Yes
Luminous flux mains mode	2300 lm
Luminous flux emergency mode	125 lm
Customs tariff number	94056120
Country of origin	Germany
EAN	4260766550010

TECHNICAL DRAWING

