



## Combined emergency luminaire Art.-No.: ROPA4201

The Highpower LED panel for suspended ceilings offers you the highest brightness of approx. 4,500 lm at the best price. That's about 135 lm per watt!

The cover is made of PMMA plastic and therefore UV resistant which prevents yellowing.

The Highpower LED Panel cleverly combines energy-saving general lighting with the prescribed emergency lighting.

- LED 33W
- IP20
- For 620mm grid ceilings



### TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Recessed ceiling
Pictograph	No
Illuminant	LED
Housing material	Metal
Mechanical rating IP	20
Impact resistance IK	≥ 3
Protection class	2
Monitoring	None
Operation time	CPS
Power consumption max.	36 W
Power consumption maintained	36 W
Power consumption non-maintained	0 W
Ambient temperature maintained mode	0 °C / 40 °C
Ambient temperature non-maintained mode	0 °C / 40 °C
Length	620 mm
Width	620 mm
Height	10 mm
Weight	3.6 kg
Weight incl. Packaging	3.68 kg
Luminous flux mains mode	3600 lm
Luminous flux emergency mode	3600 lm



Customs tariff number	94054210
Coutry of origin	CHINA
EAN	4260581710422