



Combined emergency luminaire Art.-No.: ROPA4201ML

The Highpower LED panel for suspended ceilings offers you the highest brightness of approx. 4,500 lm at the best price. That's about 135 lm per watt!

The cover is made of PMMA plastic and therefore UV resistant which prevents yellowing.

The Highpower LED Panel cleverly combines energy-saving general lighting with the prescribed emergency lighting.

- LED 33W
- IP20
- For 620mm grid ceilings



TECHNICAL DATA

Luminaire type	Combined emergency luminaire
Mounting	Recessed ceiling
Pictograph	No
Illuminant	LED
Housing material	Metal
Mechanical rating IP	20
Impact resistance IK	≥ 3
Protection class	2
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	216 V
Power consumption max.	38 W
Power consumption maintained	38 W
Power consumption non-maintained	1,5 W
Ambient temperature maintained mode	0 °C / 40 °C
Ambient temperature non-maintained mode	0 °C / 40 °C
Length	620 mm
Width	620 mm



Height	10 mm
Weight	3.67 kg
Weight incl. Packaging	3.75 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	None
Dimming function	No
Luminous flux mains mode	3600 lm
Luminous flux emergency mode	3600 lm
Customs tariff number	94054210
Coutry of origin	CHINA
EAN	4260581710439