



Art.-Nr: ROPA4202SC
General light, Emergency light Self-contained
Ceiling mounting, SelfControl (SC), 3 h, , IP20, Metal, White

LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Automatic monitoring of safety luminaire with SelfControl.



More information
www.rp-group.com/en/item/ROPA4202SC



TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	NIMH 4,8 V/4,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	36 W
Power maintained	33 W
Power non-maintained	2 W
Ambient temperature maintained mode	0 °C to 40 °C



Ambient temperature non-maintained mode	0 °C to 40 °C
Depth	620 mm
Width	620 mm
Height	10 mm
Weight	3.7
Weight incl. packaging	4.1
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	3600 lm
Luminous flux emergency	660 lm
Customs tariff number	94056120

RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main-tenance	max. luminai-res	Single luminai-re monitoring
----------	-------	------------	--------	-------	------------	---------------	-------------------	---------------------	------------------	------------------------------

As of: 29.04.2025 - Subject to technical changes and errors.