



Art.-Nr: ROPA4204SC
General light, Emergency light Self-contained
Ceiling mounting, SelfControl (SC), 3 h, , IP20, Metal, White

LED ceiling panel for general-purpose lighting with integrated safety light function for illuminating escape and emergency routes. The cover is made from PMMA plastic and is therefore UV-resistant, which prevents yellowing.

Automatic monitoring of safety luminaire with SelfControl.



More information
www.rp-group.com/en/item/ROPA4204SC



TECHNICAL DATA

Luminaire type	General light, Emergency light
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	White
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 3,2 V/4,5 Ah
Operating mode	Non-maintained
Input voltageAC	220 V
Input frequency	50 / 60 Hz
Power max.	36 W
Power maintained	33 W
Power non-maintained	2 W
Ambient temperature maintained mode	0 °C to 40 °C
Ambient temperature non-maintained mode	0 °C to 40 °C



Depth	625 mm
Width	625 mm
Height	10 mm
Weight	4.027
Weight incl. packaging	4.427
Connection cross-section	1.5 mm ²
Switching input	Yes
Battery connection	Clip
Dimming function	No
Luminous flux mains	3600 lm
Luminous flux emergency	660 lm
Customs tariff number	94056120
EAN	4260766550607

As of: 29.04.2025 - Subject to technical changes and errors.