



Art.-Nr: SGS1308SC
Emergency light Self-contained
Wall mounting, SelfControl (SC), 8 h, , IP54, Metal, Light grey

Compact emergency light equipped with one freely adjustable safety illuminants mode of metal. Suitable for inside and conditionally for outside usage. For lighting of escape and rescue routes according to EN 60598-1, EN60598-2-22 sowie EN 1838.

Automatic monitoring of safety luminaire with SelfControl.



More information
www.rp-group.com/en/item/SGS1308SC



TECHNICAL DATA

| | |
|------------------------|-----------------------------|
| Luminaire type | Emergency light |
| Mounting | Wall mounting |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Metal |
| Housing color | Light grey |
| Protection type (IP) | IP54 |
| Impact resistance (IK) | ≥ 3 |
| Certification | WEEE, CE |
| Insulation class | 1 |
| Supply | Self-contained |
| Monitoring | SelfControl (SC) |
| Bridging time | 8 h |
| Battery | AGM - OGIV 12V 12 V/21,7 Ah |
| Operating mode | Non-maintained |
| Input voltageAC | 230 V |
| Input frequency | 50 / 60 Hz |



| | |
|---|---------------------|
| Input voltage DC | 12 V |
| Power max. | 11,5 W |
| Power maintained | - W |
| Power non-maintained | 9,2 W |
| Ambient temperature maintained mode | -5 °C to 40 °C |
| Ambient temperature non-maintained mode | -5 °C to 40 °C |
| Depth | 400 mm |
| Width | 210 mm |
| Height | 300 mm |
| Weight | 22.12 |
| Weight incl. packaging | 23.07 |
| Connection cross-section | 2.5 mm ² |
| Switching input | No |
| Emergency light blocking | Yes |
| Battery connection | Clip |
| Dimming function | No |
| Luminous flux mains | - lm |
| Luminous flux emergency | 900 lm |
| Customs tariff number | 94054239 |
| EAN | 4262483025987 |



TECHNICAL DRAWING



RELATED PRODUCTS

| Art.-No. | Image | Monitoring | Supply | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires | Single luminaire monitoring |
|-----------|-------|----------------------------|----------------|----------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| SGS1308WL | | Wireless Professional (WL) | Single battery | RAL 7035 | €€ | yes | low | yes | 1,000 per system | central |

As of: 01.04.2025 - Subject to technical changes and errors.