



## Emergency luminaire Art.-No.: SGS2501SC

Compact emergency light equipped with two freely adjustable safety illuminants made of metal. Suitable for inside and conditionally for outside usage. For lighting of escape and rescue routes according to EN 60598-1, EN60598-2-22 sowie EN 1838.



### TECHNICAL DATA

|                                  |   |
|----------------------------------|---|
| Luminaire type                   | Emergency luminaire                                       |
| Mounting                         | Wall mounted  |
| Pictograph                       | No  |
| Illuminant                       | LED   |
| Housing material                 | Metal   |
| Colour                           | RAL 7035  |
| Mechanical rating IP             | 54  |
| Impact resistance IK             | ≥ 3   |
| Protection class                 | 1   |
| Supply                           | Single battery  |
| Monitoring                       | Self-Control  |
| Operation time                   | 1 h   |
| Battery                          | OGiV Longlife Series (Designlife up to 12 years and more) |
| Operation mode                   | BS  |
| Input Voltage AC                 | 230 V   |
| Input Frequency Hz               | 50 / 60 Hz  |
| Input Voltage DC                 | 12 V  |
| Power consumption max.           | 11,5 W  |
| Power consumption maintained     | - W   |
| Power consumption non-maintained | 9,2 W   |



|   |               |
|---|---------------|
| Ambient temperature maintained mode     | -5 °C / 40 °C |
| Ambient temperature non-maintained mode | -5 °C / 40 °C |
| Length                                  | 400 mm        |
| Width                                   | 210 mm        |
| Height                                  | 300 mm        |
| Weight                                  | 23.72 kg      |
| Weight incl. Packaging                  | 23.72 kg      |
| Connection cross-section                | 2.5 mm        |
| Switching input L'                      | No            |
| Emergency light blocking                | Yes           |
| Battery connector                       | Clamp         |
| Dimming function                        | No            |
| Luminous flux mains mode                | - lm          |
| Luminous flux emergency mode            | 2 x 4100 lm   |
| Customs tariff number                   | 94054239      |
| Country of origin                       | Germany       |

## TECHNICAL DRAWING

