



Emergency luminaire Art.-No.: SKS2301WL

Compact emergency light equipped with two freely adjustable safety illuminants made of metal. Suitable for inside and conditionally for outside usage. For lighting of escape and rescue routes according to EN 60598-1, EN60598-2-22 sowie EN 1838.



TECHNICAL DATA

Luminaire type	Emergency luminaire
Mounting	Wall mounted
Pictograph	No
Illuminant	LED
Housing material	Metal
Colour	RAL 7035
Mechanical rating IP	54
Impact resistance IK	≥ 3
Protection class	1
Supply	Single battery
Monitoring	WL - Wireless Professional
Operation time	1 h
Battery	OGiV Longlife Series (Designlife up to 12 years and more)
Operation mode	BS
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	12 V
Power consumption max.	11,5 W



Power consumption maintained	- W
Power consumption non-maintained	9,2 W
Ambient temperature maintained mode	-5 °C / 40 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	120 mm
Width	300 mm
Height	300 mm
Weight	14.67 kg
Weight incl. Packaging	14.67 kg
Connection cross-section	2.5 mm
Switching input L'	No
Emergency light blocking	No
Battery connector	Clamp
Dimming function	No
Luminous flux mains mode	- lm
Luminous flux emergency mode	2 x 2500 lm
Customs tariff number	94054239
Coutry of origin	Germany
EAN	4260659563776

TECHNICAL DRAWING

