




## Emergency luminaire Art.-No.: WAF029ML-E

LED emergency luminaire for surface wall mounting for the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and DIN EN 1838. It is harmonized with the design of the WEF or WER recessed wall luminaires and fit together with the exit signs of the A-series.



### TECHNICAL DATA

Luminaire type	Emergency luminaire
Mounting	Wall mounted
Pictograph	No
Illuminant	LED
Housing material	Zinc die casting
Colour	Stainless steel look
Mechanical rating IP	20
Impact resistance IK	4
Protection class	2
Supply	Central power supply system
Monitoring	ML - Central power supply system
Operation time	CPS
Operation mode	single luminaire switching
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	216 V
Power consumption max.	4,5 W
Power consumption maintained	4,5 W
Power consumption non-maintained	1,1 W
Ambient temperature maintained mode	-20 °C / 35 °C
Ambient temperature non-maintained mode	-20 °C / 40 °C
Length	53 mm
Width	193 mm
Height	115 mm
Weight	0.07 kg



Weight incl. Packaging	0.1 kg
Connection cross-section	2.5 mm
Switching input L'	Yes
Emergency light blocking	No
Battery connector	None
Dimming function	Yes
Luminous flux mains mode	420 lm
Luminous flux emergency mode	420 lm
Customs tariff number	94056180
Coutry of origin	Germany
EAN	4260581712891

## TECHNICAL DRAWING

