



Art.-Nr: WER021SC-AZ
Emergency light Self-contained
Recessed wall mounting, SelfControl (SC), 1 h, , IP20, Zinc die-cast, Anthracite

High-grade zinc die-cast safety luminaire for recessed mounting in the wall.

This is intended for mounting in conventional switch boxes where the mounting frame can be aligned to the box. The zinc die-cast ornamental cover is locked using a fastener that cannot be seen from the outside. Since the status LED is fitted in the light source, the harmony of the housing is not interrupted.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/WER021SC-AZ



TECHNICAL DATA







Luminaire type	Emergency light
Mounting	Recessed wall mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	Anthracite
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	NIMH 4,8 V/2,0 Ah
Operating mode	Non-maintained / maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Power max.	3,1 W
Power maintained	1,7 W








Power non-maintained	0,35 W
Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	20 mm
Width	90 mm
Height	90 mm
Installation dimensions Diameter	68 mm
Weight	0.45
Weight incl. packaging	0.58
Connection cross-section	2.5 mm ²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Luminous flux mains	140 lm
Luminous flux emergency	140 lm
Customs tariff number	94056180
GTIN	4260682144225



TECHNICAL DRAWING





As of: 25.07.2025 - Subject to technical changes and errors.