



Emergency luminaire Art.-No.: WER021WL

LED emergency luminaire for wall installation for the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 605982-22 and DIN EN 1838. This recessed luminaire is designed for installation in conventional jacks. The mounting frame can be aligned with the jack. The zinc-aluminum cover is locked without externally visible fastening. Through the status LED which is incorporated in the lens the harmony of the housing is not interrupted.



TECHNICAL DATA

Luminaire type	Emergency luminaire
Mounting	Recessed wall
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Colour	RAL 9003
Mechanical rating IP	20
Impact resistance IK	≥ 3
Protection class	2
Supply	Single battery
Monitoring	WL - Wireless Professional
Operation time	1 h
Battery	4,8V/2,0Ah NiMH
Operation mode	maintained/non-maintained mode
Input Voltage AC	230 V
Input Frequency Hz	50 / 60 Hz
Input Voltage DC	- V
Power consumption max.	5,6 W



Power consumption maintained	5,2 W
Power consumption non-maintained	3,8 W
Ambient temperature maintained mode	-5 °C / 40 °C
Ambient temperature non-maintained mode	-5 °C / 40 °C
Length	90 mm
Width	19 mm
Height	90 mm
Install. dim. diameter	68 mm
Weight	0.51 kg
Weight incl. Packaging	0.64 kg
Connection cross-section	1.5 mm
Switching input L'	Yes
Emergency light blocking	Yes
Battery connector	Clamp
Dimming function	No
Luminous flux mains mode	140 lm
Luminous flux emergency mode	140 lm
Customs tariff number	94056180
Coutry of origin	Germany
EAN	4260659564063



TECHNICAL DRAWING

