



Emergency luminaire Art.-No.: WER023WL-E

LED emergency luminaire for wall installation for the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 605982-22 and DIN EN 1838. This recessed luminaire is designed for installation in conventional jacks. The mounting frame can be aligned with the jack. The zinc-aluminum cover is locked without externally visible fastening. Through the status LED which is incorporated in the lens the harmony of the housing is not interrupted.



TECHNICAL DATA

| | |
|----------------------------------|--------------------------------|
| Luminaire type | Emergency luminaire |
| Mounting | Recessed wall |
| Pictograph | No |
| Illuminant | LED |
| Housing material | Zinc die-cast |
| Colour | Stainless steel look |
| Mechanical rating IP | 20 |
| Impact resistance IK | ≥ 3 |
| Protection class | 2 |
| Supply | Single battery |
| Monitoring | WL - Wireless Professional |
| Operation time | 3 h |
| Battery | 4,8V/2,0Ah NiMH |
| Operation mode | maintained/non-maintained mode |
| Input Voltage AC | 230 V |
| Input Frequency Hz | 50 / 60 Hz |
| Input Voltage DC | - V |
| Power consumption max. | 5,6 W |
| Power consumption maintained | 5,2 W |
| Power consumption non-maintained | 3,8 W |



| | |
|---|---------------|
| Ambient temperature maintained mode | -5 °C / 40 °C |
| Ambient temperature non-maintained mode | -5 °C / 40 °C |
| Length | 20 mm |
| Width | 90 mm |
| Height | 90 mm |
| Install. dim. diameter | 68 mm |
| Weight | 0.51 kg |
| Weight incl. Packaging | 0.64 kg |
| Connection cross-section | 1.5 mm |
| Switching input L' | Yes |
| Emergency light blocking | Yes |
| Battery connector | Clamp |
| Dimming function | No |
| Luminous flux mains mode | 140 lm |
| Luminous flux emergency mode | 140 lm |
| Customs tariff number | 94056180 |
| Coutry of origin | Germany |
| EAN | 4260682147387 |



TECHNICAL DRAWING

